

The flat surface is the top result.

Machines that enable professionals to literally and figuratively – go any way they want. The SUPER-SCREED is light yet robust and very easy to handle – therefore, manoeuvring is simple. The machines guarantee maximum reliability and high productivity. Perfectly levelled, flat floors; regardless how small or big the surface is.

FEATURES AND BENEFITS

- Levelling without guiding rails.
- Protected and integrated excentric element.
- Adjustable handle with mounted throttle.
- Foldable drive unit.
- Perfectly chromed frame, easy to clean.
- Two standards lengths 1,8 m and 3,6 m.
- Platform compatible with ECO-VIB concrete vibrator.



OPTIMUM POWER AND PERFORMANCE



Transport box for 2 batteries and a fast charger. Supplied with one battery, second battery on request as an option.



Code	400.00.10000	400.00.18000	400.00.36000
Model	Drive unit & Blade	Blade 1,8 m	Blade 3,5 m



Code	400.00.10000	400.00.11006ECO
Model	SUPER-SCREED	ECO-SCREED*
Weight (kg)	15,5	15
Engine	Honda GX35	Battery 70 min - 5 A
Type of engine	Four stroke gasoline air cooling 1 cylinder	PACLITE Innovation
Cylinder (cm³)	35,8	-
Engine power kW (hp)	1,2 (1,6)	0,5
At (rpm)	7000	7000
Capacity of fuel tank (l)	0,65	-
Consumption of fuel (l/h)	0,6	-
Length (mm)	1117	1117
Width (mm)	889	889
Hand-arm vibration according to ISO 5349 on fresh concrete (m/s²)	3,1	3,1
Guaranteed sound-power level, LWA dB (A)	83	83
Sound pressure level (at operator's ear) dB (A)	70	70