

Versatile, high performance forward plate compactor


Premium asphalt plates feature a durable base plate for various applications. A true combination plate for various applications in the 85-90kg weight class.

Designed for the compaction of granular and mixed materials with some cohesive content in confined areas such as parking lots, highway and bridge construction, next to structures, curbs, and abutments. This computer designed base plate has a tapered bottom and edges for high speed and excellent manoeuvrability.

FEATURES AND BENEFITS


- Straight, centre-mounted guide handle offers superior manoeuvrability and can be lowered within inches of the surface to operate plate under obstacles and form work.
- Many lifting points and front lift cage offer easier loading and unloading for operator convenience.
- Compact design, easy to use, cast bottom plate.Smooth and flexible.
- Throttle mounted on the operating handle.





* Recommended thickness of layer

OPTION : PAVING PAD		
Code	PPV-PAD400	
	PPV-PAD450	



Code	V400COMBI	V400-ECO	
Model	V400 COMBI	V400 ECOPOWER	
Operating mass (kg)	92	97	
Centrifugal force (kN)	14	14	
Plate width (mm)	400	400	
Engine	Honda GX160	Honda EGX	
Net power hp (kW)	4,8 (3,6)	2,4 (1,8)	
Rated engine speed (rpm)	3600	3600	
Fuel tank capacity (L)	3,1	-	
Engine oil capacity (L)	0,6	-	
Fuel consumption at rated power (L/h - rpm)	1,4 - 3600	-	
Water tank (L)	13	13	
Speed (m/min)	21	25	
Amplitude (mm)	0,89	0,89	
Frequency (Hz)	95	95	
Sound pressure level dB (A)	91	55	
Vibrations* (m/s ²)	2,62	3,62	
Surface capacity (m²/h)	685	805	
* Minimum vibration levels measured to EN500-4			
Certified power SAE J 1349			





Option: Accessory - stone paving pad, essential accessory for the installation of slabs or pavers.