

## Submersible flexible shaft pump 72 m<sup>3</sup>/h

Submersible pump for draining and removal of water from trench sand building sites without use of electric power. The FORCE pump can take aggregates as large as 15 mm and offers a more rugged heavy duty design.

## FEATURES AND BENEFITS

- Pump with high output and a capacity of 72 m<sup>3</sup>/h.
- Cast steel impeller.
- Solid size capacity: 15 mm.
- High quality components and strong flexible shaft, 6 m.
- Two-dog coupling identical to FP poker vibrators which enable compatibility and versatility in utilisation between water removal and concreting work.
- Autonomous, portable and lightweight in size, this pump can be used in a multitude of applications.
- Same engine power units used together with FP-37-DC poker vibrators.
- Standard delivery with discharge hose of 10 meters and 3" (75 mm), fireman's quick release coupling.
- Engine Honda GX160.
- 2800 rpm, max. head height 15 m.
- Flexible shaft hose 6 meters long.



norm SAE J1349



POWERED by HONDA



Stainless steel impeller



FP Couplings compatible with PPF-80 pump



PACK VIB 35 mm + PUMP

COMPLETE PUMP	
PPF80-H	Complete pump 6 m with accessories included + fireman couplings + discharge hose 10 m + Motor Honda GX160
PPF80 Diesel	Complete pump 6 m with accessories included + fireman couplings + discharge hose 10 m + motor HATZ diesel 1B20
PPF80-E 230V	Complete pump 6 m with accessories included + fireman couplings + discharge hose 10 m + motor 230 volt-1-50Hz
104.10.00306	Pack pump set complete + flexible shaft poker FP-37-DC
PUMP PPF80-H OPTIONS	
PPF80P-SH-10M	Fireman coupling mounted to 10 m flat hose
PPF80P-SH-20M	Fireman coupling mounted to 20 m flat hose
PPF80-Pompe	Pump only (shaft + strainer) without accessories
PPF80-PUMP	Strainer only : Pump core
PPF80-OIC	Flexible shaft complete 6 m (inner and exterior part with couplings)
PPF80-FLI	Complete inner flexible shaft 6 m
Certified power SAE J 1349	



Force Pump core

