

# ECO 500 & ECO 300 DUMPER -NEW!

## Battery operated dumpers



### Battery-operated dumpers 300 and 500 kg

Take your projects to the next level with the PacLite ECO 500 Dumper, a powerhouse designed to tackle the toughest tasks across the construction, hire, and manufacturing industries. Whether it's interior demolition, landscaping, utility work, or general construction, this versatile machine is built to handle it all—even on the most challenging terrains.

Boost productivity and safety on-site with its cutting-edge features, reducing labour costs and ensuring seamless operation. Its compact size and articulated steering make navigating tight spaces effortless, while the battery-powered design delivers up to 8 hours of runtime with zero emissions—perfect for indoor or noise-sensitive environments.





### FEATURES AND BENEFITS




- **Unmatched capacity:** a 500 kg or 300 kg poly tray for heavy loads, easy cleaning, and reduced noise.
- **Simplified operation:** the two-stage self-tipping skip eliminates manual lifting.
- **Ultimate efficiency:** a superior tip angle ensures the skip is completely emptied every time.
- **Precision manoeuvring:** the articulated steering lets you navigate even the tightest spaces with ease.
- **Eco-friendly performance:** battery-powered for zero emissions and whisper-quiet operation.
- **Enhanced safety:** equipped with an electric brake system and safe parking mode.
- **Unstoppable power:** constant electric transaxle 4WD for outstanding traction on all terrains.
- **Compact versatility:** offset rim wheels reduce width to just 730 mm, perfect for standard doorways.
- **Built to last:** a low-maintenance, fully sealed drive system with no gearboxes or belts.

Upgrade your machine with optional accessories, including a Tow Ball Hitch, Flat Bed, Narrow Steel Bucket, Skip Control Handle, and Turf Tyre Wheels.

ECO 500 DUMPER



ECO 300 DUMPER



| Code                   |  | HTL500-ECO            | HTL300-ECO            |
|------------------------|--|-----------------------|-----------------------|
|                        | <b>Model</b>                             | <b>ECO 500 DUMPER</b> | <b>ECO 300 DUMPER</b> |
|                        | Loading capacity (kg)                    | 500                   | 300                   |
|                        | Bucket capacity (cbm)                    | 0,30 cbm              | 0,2                   |
|                        | Rated output (W)                         | 830                   | 2 x 1, 5              |
| <b>SPEED</b>           |  |                       |                       |
|                        | Max travel speed (km/h)                  | 6,0                   | 5,7/2,2               |
|                        | Rotating speed (rpm)                     | 2200                  | 1500                  |
|                        | Climbing capacity (%)                    | 20                    | 46-35                 |
| <b>BATTERY</b>         |  |                       |                       |
|                        | Type                                     | Lithium battery       |                       |
|                        | Battery capacity (kW)                    | 1,5                   |                       |
| <b>MAIN DIMENSIONS</b> |  |                       |                       |
| A                      | Wheel base (mm)                          | 800                   | 778                   |
| B                      | Length (mm)                              | 2078                  | 1695                  |
| C                      | Height (mm)                              | 1013                  | 1009                  |
| D                      | Width (mm)                               | 889                   | 782                   |
| E                      | Tire width (mm)                          | 160                   | 160                   |
| F                      | Minimum Height (mm)                      | 122                   | 124                   |
| G                      | Hopper top height when unlocking (mm)    | 1398                  | 1189                  |
| H                      | Hopper bottom height when unlocking (mm) | 176                   | 228                   |
| I                      | Hopper tilting angle                     | 80°                   | 66°                   |
| J                      | Hopper right turn angle                  | 35°                   | 35°                   |
| K                      | Hopper left turn angle                   | 35°                   | 35°                   |
| L                      | Handle bar right turn angle              | 49°                   | 49°                   |
| M                      | Handle bar left turn angle               | 49°                   | 49°                   |

COMPACTON

MOBILE EQUIPMENT

CONCRETE EQUIPMENT

SURFACING

CUTTING - GRINDING