## PACLITE M900-ECO VANGUARD: The Future of Troweling – Zero Emissions, Maximum Performance

PACLITE continues to lead the way in innovation with the M900-ECO, a battery-powered trowel designed for zero CO<sup>2</sup> emissions without compromising performance. The green "E" in our Zero Emission line represents more than just the power source, it stands for a cleaner, more sustainable way of working.

## FEATURES AND BENEFITS

- Uncompromised Performance: delivers the same power and efficiency as conventional trowels.
- High-Speed Burnishing: reaches up to 145 RPM, thanks to a heavy-duty gearbox and PACLITE's patented drive system.
- Lower Operating Costs: a virtually maintenance-free electric motor reduces the total cost of ownership.
- Eco-Friendly & Quiet: no exhaust gases, no noise, ideal for indoor use, and low-emission zones.
- User & Environmental Safety: designed for urban job sites, interior spaces, and emission-restricted areas.
- Go green without sacrificing power: choose the PACLITE M900-ECO for a cleaner, quieter, and more cost-effective way to get the job done.
- Delivered with charger & one interchangeable battery.



ModelM900-ECOFold handleYesBattery Litium ION (A)60 V - 40 (A) HBattery charger71.4 V - 25 (A) HCharging time -full charge (min)45Charging time -full charge (min)45No. batteries2Running with pan (min)45Running with finishing blades (min)70Epoxy colorYellowEngine3000W Golden Motor HPM30KW DC brushlessRunning stepless (rpm)0 to 140Guaranteed sound-power level, LWA dB (A)45Sound pressure level (at operator's ear) dB (A)35Dimensions Folded (mm)1305 x 992Dimensions W x H x L (mm)992 x 781 x 2013Hand-arm vibration according to ISO 5349 on fresh concrete (m/s²)2,1	Code	ECO-900M
Battery Litium ION (A) $60 \vee -40 (A) H$ Battery charger $71.4 \vee -25 (A) H$ Charging time -full charge (min) $45$ No. batteries $2$ Running with pan (min) $45$ Running with finishing blades (min) $70$ Epoxy colorYellowSound pressure level $3000W$ Golden Motor HPM30KW DC brushlessRunning stepless (rpm) $0$ to $140$ Guaranteed sound-power level, LWA dB (A) $45$ Sound pressure level (at operator's ear) dB (A) $35$ Dimensions Folded (mm) $1305 \times 992$ Dimensions W x H x L (mm) $992 \times 781 \times 2013$ Hand-arm vibration according to ISO 5349 on fresh concrete (m/s <sup>2</sup> ) $2,1$	Model	M900-ECO
Battery charger71,4 V - 25 (A) HCharging time -full charge (min)45No. batteries2Running with pan (min)45Running with finishing blades (min)70Epoxy colorYellowEngine3000W Golden Motor HPM30KW DC brushlessRunning stepless (rpm)0 to 140Guaranteed sound-power level, LWA dB (A)45Sound pressure level (at operator's ear) dB (A)35Dimensions Folded (mm)1305 x 992Dimensions W x H x L (mm)992 x 781 x 2013Hand-arm vibration according to ISO 5349 on fresh concrete (m/s²)2,1	Fold handle	Yes
Charging time -full charge (min)45No. batteries2Running with pan (min)45Running with finishing blades (min)70Epoxy colorYellowEngine3000W Golden Motor HPM30KW DC brushlessRunning stepless (rpm)0 to 140Guaranteed sound-power level, LWA dB (A)45Sound pressure level (at operator's ear) dB (A)35Dimensions Folded (mm)1305 x 992Dimensions W x H x L (mm)992 x 781 x 2013Hand-arm vibration according to ISO 5349 on fresh concrete (m/s²)2,1	Battery Litium ION (A)	60 V - 40 (A) H
No. batteries2Running with pan (min)45Running with finishing blades (min)70Epoxy colorYellowEngine3000W Golden Motor HPM30KW DC brushlessRunning stepless (rpm)0 to 140Guaranteed sound-power level, LWA dB (A)45Sound pressure level (at operator's ear) dB (A)35Dimensions Folded (mm)1305 x 992Dimensions W x H x L (mm)992 x 781 x 2013Hand-arm vibration according to ISO 5349 on fresh concrete (m/s²)2,1	Battery charger	71,4 V - 25 (A) H
Running with pan (min)45Running with finishing blades (min)70Epoxy colorYellowEngine3000W Golden Motor HPM30KW DC brushlessRunning stepless (rpm)0 to 140Guaranteed sound-power level, LWA dB (A)45Sound pressure level (at operator's ear) dB (A)35Dimensions Folded (mm)1305 x 992Dimensions W x H x L (mm)992 x 781 x 2013Hand-arm vibration according to ISO 5349 on fresh concrete (m/s²)2,1	Charging time -full charge (min)	45
Running with finishing blades (min)70Epoxy colorYellowEngine3000W Golden Motor HPM30KW DC brushlessRunning stepless (rpm)0 to 140Guaranteed sound-power level, LWA dB (A)45Sound pressure level (at operator's ear) dB (A)35Dimensions Folded (mm)1305 x 992Dimensions W x H x L (mm)992 x 781 x 2013Hand-arm vibration according to ISO 5349 on fresh concrete (m/s²)2,1	No. batteries	2
Epoxy colorYellowEngine3000W Golden Motor HPM30KW DC brushlessRunning stepless (rpm)0 to 140Guaranteed sound-power level, LWA dB (A)45Sound pressure level (at operator's ear) dB (A)35Dimensions Folded (mm)1305 x 992Dimensions W x H x L (mm)992 x 781 x 2013Hand-arm vibration according to ISO 5349 on fresh concrete (m/s²)2,1	Running with pan (min)	45
Engine3000W Golden Motor HPM30KW DC brushlessRunning stepless (rpm)0 to 140Guaranteed sound-power level, LWA dB (A)45Sound pressure level (at operator's ear) dB (A)35Dimensions Folded (mm)1305 x 992Dimensions W x H x L (mm)992 x 781 x 2013Hand-arm vibration according to ISO 5349 on fresh concrete (m/s²)2,1	Running with finishing blades (min)	70
EngineHPM30KW DC brushlessRunning stepless (rpm)0 to 140Guaranteed sound-power level, LWA dB (A)45Sound pressure level (at operator's ear) dB (A)35Dimensions Folded (mm)1305 x 992Dimensions W x H x L (mm)992 x 781 x 2013Hand-arm vibration according to ISO 5349 on fresh concrete (m/s²)2,1	Epoxy color	Yellow
Guaranteed sound-power level, LWA dB (A)45Sound pressure level (at operator's ear) dB (A)35Dimensions Folded (mm)1305 x 992Dimensions W x H x L (mm)992 x 781 x 2013Hand-arm vibration according to ISO 5349 on fresh concrete (m/s²)2,1	Engine	
Sound pressure level (at operator's ear) dB (A)35Dimensions Folded (mm)1305 x 992Dimensions W x H x L (mm)992 x 781 x 2013Hand-arm vibration according to ISO 5349 on fresh concrete (m/s²)2,1	Running stepless (rpm)	0 to 140
(at operator's ear) dB (A)35Dimensions Folded (mm)1305 x 992Dimensions W x H x L (mm)992 x 781 x 2013Hand-arm vibration according to ISO 5349 on fresh concrete (m/s²)2,1	Guaranteed sound-power level, LWA dB (A)	45
Dimensions W x H x L (m)992 x 781 x 2013Hand-arm vibration according to ISO 5349 on fresh concrete (m/s²)2,1		35
Hand-arm vibration according to ISO 5349 on fresh concrete (m/s <sup>2</sup> ) 2,1	Dimensions Folded (mm)	1305 x 992
on fresh concrete (m/s <sup>2</sup> ) Z, 1	Dimensions W x H x L (mm)	992 x 781 x 2013
Weight (kg) 109		2,1
	Weight (kg)	109



VANGUARA

VANGUARD BATTERY