The Mechanical PRT168 ride-on trowel is equipped with a high-horsepower gasoline engine, heavy-duty drive trains, and packed in easy-to-service frames.

Our heavy-duty gear box and four-bladed rotors are proven performers in the field. PACLITE PRT rider combines exceptional performance with a perfect balance.

It allows quick finishing of a large concrete surface, and, at the same time, ensures it is flat and smooth.

## FEATURES AND BENEFITS

- Independent manual pitch control.
- Raised foot pedals.
- Powered retardant spray system.
- Centrifugal clutch.
- Five-blade spider with heavy-duty gearbox.
- Four lights.
- Safety switch built-into the seat.
- Epoxy-painted structure.
- Option: transport trolley with inflatable wheels.



Code P	
Model P	
W x H (mm) 1980 X	Dimension L x W
weight (kg)	Operating we
width (mm)	Panning path wi
meter (mm)	Rotors diame
peed (rpm) 110	Maximum rotor spe
Engine Hond	
wer hp (kW) 22,	Net powe
	Rated engine spe
1 3 0	Fuel tank ca
1 5 ( )	Engine oil ca
consumption 6,7 er (L/h - rpm)	Fuel con at rated power (I
pray system Pre	Spra
Application Finishin	Ар
ration (m/s²)	Hand vibrati
wer kW (hp) 16,	Rated Powe
ration (m/s²)	Foot vibrati
ration (m/s²)	Seat vibrati
teed dB (A)	Sound level guarantee
level dB (A)	Sound pressure lev
er SAE J 1349	Certified power
ptions Coc	Opti
	Trowel pans with 8 inserts for left and right ro (2 per machi
chine) 947-05	Set of 4 blades (8 blades per machi
50 mm <b>PRT168M</b> -	Slings 6 inches 150 r



Two water tanks




Cup holder



Transport wheels 'Dolly jacks'



Electric spray system in handle



Transport wheels 'Dolly jacks' 2/set

PRT168M-027684

1040