

M900/Lightweight and foldable handle
M1200 heavy-duty and foldable handle

The Series Master 900 and Master 1200 incorporates amazing balance, improved serviceability, and your choice of wide or narrow frame, straight or foldable handle, providing contractors with the ideal machine for residential and general construction work. The large Master 1200 is designed for high speed burnishing up to 180 rpm with a HD gearbox and PACLITE patented drive system.

PACLITE "": Get a grip on the best". Our new anti-vibration handle design dramatically reduces the vibration transmitted to the operator. These height-adjustable handles will increase operator comfort and decrease fatigue over an eight-hour day.

FEATURES AND BENEFITS

- The handle is of an ergonomically sound design with all operating controls easily accessible for the operator from the driving position.
- The handlebar acts as a "dead man's grip" safety device and can be reached from any gripping position on the handle.
- The speed selection is made with a switch on the handle.
- The change of the blade angle is made with a circular adjuster on the handle. The blades are reversible for double life.
- The trowel is equipped with two carrying handles for manual raising.
- M900 and M1200 are equipped with a chromed frame.
- New detachable transport wheel kit.



M900



POWERED by **HONDA**
norm SAE J1349



M900 CC

Foldable and compact model

Code	M900-CC	M900 Manual	M900EP	M1200-CC
Model	M900 CC Honda	M900 MANUAL	M900-EP230V	M1200 CC Honda
Operating weight (kg)	75	75	75	113
Dimensions folded (mm)	1305 x 992	1305 x 992	1305 x 992	1408 x 1200
Dimensions W x H x L (mm)	2013 x 992 x 781	2013 x 992 x 781	2013 x 992 x 781	2130 x 1206 x 1008
Trowelling diameter (mm)	925	925	925	1170
Number of blades	4	4	4	4
Trowelling speed (rpm)	65-131	65-131	65-131	65-131
Engine	Honda GX200	Honda GX200	-	Honda GX270
Net power hp (kW)	5,8 (4,3)	5,8 (4,3)	4,8 (3,6)	8,4 (6,3)
Rated engine speed (rpm)	3600	3600	1500	3600
Fuel tank capacity (L)	3,1	3,1	-	5,3
Engine oil capacity (L)	0,6	0,6	-	1,1
Fuel consumption at rated power (L/h - rpm)	1,4 - 3600	1,4 - 3600	-	2,4 - 3600
Hand-arm vibration according to ISO 5349 on fresh concrete (m/s ²)	3,8	3,8	3,1	4,1
Guaranteed sound-power level, LWA dB (A)	95	95	75	99
Sound pressure level (at operator's ear) dB (A)	84	84	69	90
Consumption (l/h)	1	1	-	1,8
Shaft	Foldable	Straight	Foldable	Foldable
Dead man's safety handle	Yes	Yes	Yes	Yes
Clutch	Centrifugal	Manual with Dead man's safety Handle	Manual with Dead man's safety Handle	Centrifugal

Certified power SAE J 1349



Throttle



Security switch



Transport Wheels Models 900

PPT WHEELS 900



The PACLITE gearboxes are the most reliable in the industry for years of maintenance free operation.

COMPACTON

MOBILE EQUIPMENT

CONCRETE EQUIPMENT

SURFACING

CUTTING - GRINDING